



Your Single Source Solution

Ductless EZ-Pull® Line Sets for HVACR Applications

Ductless mini-split systems. VRF commercial systems

Job Name

Contractor

Job Location

Wholesaler

Engineer

JMF Rep

APPLICATION - FEATURES

- Meets ASTM E84 for smoke and fire (25/50)
- Rugged, anti-tear exterior allows for easier installation of the line set
- R410 A Approved
- Paintable
- Available in BLACK or WHITE hard shell
- Superior tear resistance
- UV Resistant
- Insulation is marked every foot
- 45° Forged Flare Nuts

TECHNICAL SPECIFICATIONS

Copper Tubing: Manufactured according to ASTM B280 and meets ASTM B1003 - Standard Specification for Seamless Copper Tube for Linesets.

Copper: No. C122200 DHP (Phosphorous deoxidized, high residual phosphorous)

Low-density Polyethylene Foam: Closed cells foam, CFC and HCFC gas free

Insulation: According to ASTM E96-00

Working Temperature: Meets/exceeds ASTM C 1427-07

Surface Burning Characteristics: UL 94HBT, UL 723, ASTM E84 (25/50), flame and spread index less than 25 and smoke development index less than 50 as tested according to UL 723.

EZ-Pull - Insulation (White or black hard shell)

Both Lines Insulated

Tube Sizes	Lengths
1/4" - 5/8"	25' - 50'

Insulation Wall Thickness: 1/2" & 3/4"

INSULATION R VALUES

1/2" Wall - R3.3 MINIMUM

3/4" Wall - R5.2

1" Wall - R7.2

*R - Value calculation using a K-Factor of 0.25

BTU-in/hr-ft (2)-F @ 75°F, 24°C mean temp.

JMF COMPANY IS YOUR CONSOLIDATING SOURCE FOR copper tubing, line sets, copper fittings, push to fit, pex, ball valves, gas valves, plumbing valves, malleable fittings, steel nipples, plastic fittings, brass threaded, brass nipples, flare & compression, gas connectors, water connectors, appliance kits, cord sets and MORE.

